

INITIAL	START	RUN-UP	TAKEOFF	DESCENT	AFTER LANDING
Weather & Den. Alt. Weight & Balance Performance Req. Flight Plan – File Papers – A.R.O.W. Fuel – Both Control Lock Master – On Flaps – Extend Pitot Heat – Test Lights – Int. / Ext. Fuel Gauges – True Master – Off EXTERIOR SUMMARY <i>After Thorough Geographical Check</i> Fuel Quantity Fuel Quality Caps / Drains / Vents Engine / Oil / Belt Prop / Air Intake Exhaust System Stall Indicator – Test Surfaces & Controls Pitot & Static Ports Gear / Tires / Brakes Antennas Ties/Chocks/Towbar Baggage Door Final Walk Around INTERIOR Passenger Brief Hobbs / Tach Time Circuit Breakers Alternate Static	Seat Track/Back – Lock Avionics – Off Autopilot – Off Carb Heat – Off Mixture – Full Rich Throttle – Slight Prime Brakes Prop – Clear Master – On Beacon – On Mags – Start Oil Pressure Lights – As Req. Mixture – As Req. PRE-TAXI / TAXI Seat Belts / Harness Flaps – Up Heat / Vent / Defrost Avionics – On ATIS / AWOS Altimeter XPDR – Alt + Sqwk ADS-B – On Radio – Test Taxi Light – As Req. Brakes – Test Attitude Indic. – Test Turn Coord. – Test H.I. To Compass – Test	Brakes Fuel – Both Trim – Takeoff Flight Controls / AP Instruments Mixture – Best Power Primer – In & Lock 1700 RPM Mags-Test <i>R-L-Both</i> Carb Heat – Test Vacuum Amps / Volts Oil Pressure Oil Temperature Idle – Check Closed Throttle Friction PRE-TAKEOFF Flaps – 0°-10° Mixture – Best Power Carb Heat-Off <i>Or As Req.</i> Pitot Heat – As Req. XPDR – Alt + Sqwk Heading Bug Doors / Windows Landing Light – On Strobes – On Time – Note Brakes – Release <i>ABORT PLAN-READY!</i>	Full Throttle 2260 RPM <i>Minimum</i> Oil Pressure Rotate – *52 (60) Vy – 71 (82) Flaps – Up CLIMB 70-78 (80-90) Power Mixture Instruments Taxi / Land Light – Off Flight Plan – Open CRUISE Power Mixture Instruments	Mixture – Richen Fuel – Both Carb Heat – As Req. ATIS / AWOS Altimeter Instruments PRE-LANDING Brakes – Pedal Test Landing Light – On Autopilot – Off Seat Belt / Harness Mixture – Best Power Carb Heat – On Fuel – Both Flaps – As Req. LANDING Flaps – 40° <i>Or As Req.</i> * 61 (70) <i>G.U.M.P.F.S.</i> GO-AROUND Power – Full Carb Heat – Off Positive Rate Climb Flaps – Retract Slowly	Flaps – Up Carb Heat – Off Strobes – Off Landing Light – Off Taxi Light – As Req. Pitot Heat – Off Mixture – As Req. Trim – Takeoff XPDR – Alt + Sqwk SECURING ELT – Verify Silent Avionics – Off Mixture – Full Lean Mags – Off Master – Off Fuel – Left or Right Lights – Off Hobbs / Tach Time Control Lock Chocks Tie Downs Pitot Cover Baggage Door Cabin Doors Close Flight Plan * Adjust Speed As Needed For Conditions. Check Your POH For Notes / Cautions Plus Manufacturer For Revisions.

Vr • Rotation –	52 (60)	Vs0 • Stall With Flaps –	43 ⁽¹⁾ (49)	Va • Max Abrupt (2000 lbs) –	99 (114)	Vfe • Full Flaps –	87 (100)
Vx • Best Angle Climb –	59 (68)	Vs • Stall w/o Flaps –	50 ⁽¹⁾ (57)	Va • Max Abrupt (Full Gross) –	106 (122)	X Wind • Max Demo'd –	13 (15)
Vy • Best Rate Climb –	71 (82)	Best Glide (2000 lbs) –	65 (75)	Vno • Max Structural Cruise –	122 (140)		
		Best Glide (Full Gross) –	70 (80)	Vne • Never Exceed –	151 (174)		

	KNOTS (MPH)	FLAPS °	– NOTES –
DEPARTURE			
Rotation *	52 (60)	0	⁽¹⁾ Stall Speeds Are CAS
Best Angle Climb	59 (68)	0	Short Field With Obstacle: 0° Flaps
Best Rate Climb	71 (82)	0	Short w/o Obstacle or Soft: 10° Flaps
CRUISE TAS-5,000'			
Economy	95 (109)	0	2300 RPM – 6.5 GPH – 55%
Normal	107 (123)	0	2500 RPM – 7.4 GPH – 68%
Maximum	112 (129)	0	2600 RPM – 8.1 GPH – 75%
ARRIVAL			
Approach	70 (80)	10-20	1700 RPM (Initially)
Short Final *	61 (70)	30-40	Idle-1200 RPM

WARNING: Permission to use this CheckMate® is granted to the authorized purchaser only. No warranties, either express or implied, of any kind, are made hereunder, including, but not limited to any warranties for fitness for particular use. The information contained herein varies according to individual aircraft, model, and year of manufacturer and while we believe the information to be accurate, no representations are made as to the degree of accuracy of the information. This information constitutes only partial information necessary to properly operate an aircraft and is not to be used as a substitute for the use of other information sources routinely used in the operation of aircraft or the acquisition of requisite training to operate aircraft. Purchaser assumes all risk of use in using this product. Purchaser consents to and understands that CheckMate Aviation Inc., or any related entity, bears no liability for the use of this product.

Specs Are Approximate Because Of Environment & Plane Model / Year Variables. Specs Are In: LBS, KIAS, Sea Level, Standard Day, Normal Category, Max. Gross Wt., No Wind, "Best Power", Wheel Pants, New Engine. () = MPH.
ALL RIGHTS RESERVED 8.51
 CheckMate Aviation Inc. 800-259-3741 1992-2023

(IF UNABLE TO ABORT TAKEOFF)

POWER LOSS IMMEDIATELY AFTER TAKEOFF / NO RESTART

MAINTAIN AIRCRAFT CONTROL

BEST GLIDE – 70 KIAS (80 MPH) *Full Gross Weight*

FUEL SELECTOR – OFF

MIXTURE – FULL LEAN / IDLE CUTOFF

FLAPS – DOWN

MASTER & MAGS – OFF

*UNLATCH DOORS
PROTECT BODY*

POWER LOSS IN FLIGHT

BEST GLIDE – 70 KIAS (80 MPH) *Full Gross Weight*

CARB HEAT – ON *Also Supplies Alternate Air*

NOTE WIND DIRECTION & VELOCITY

PICK LANDING SITE

MIXTURE – FULL RICH

FUEL SELECTOR – CHECK / SWITCH / BOTH *Note Gauges*

FUEL PRIMER – LOCKED *Try Re-Priming*

MAGNETOS – CHECK ALL

MASTER – ON

IF NO RESTART & TIME PERMITS

MAINTAIN BEST GLIDE

SQUAWK 7700

DECLARE EMERGENCY *TWR, APP, Unicom, 121.5*

MIXTURE – FULL LEAN / IDLE CUTOFF

FUEL SELECTOR – OFF

SEATBELTS / HARNESS

FLAPS – AS NEEDED *Full Flaps When Field Assured*

MASTER & MAGS – OFF

UNLATCH DOORS

PROTECT BODY

ELECTRICAL FIRE IN FLIGHT

ALL ELECTRICAL DEVICES + MASTER OFF *Mags – On*

CABIN HEAT & AIR – OFF

IF FIRE OUT – MASTER ON ONLY IF CRITICAL *Vents – Open*

THEN ONE ESSENTIAL ELECTRICAL DEVICE AT A TIME

RESET CIRCUIT BREAKER ONLY IF CRITICAL

ENGINE FIRE IN FLIGHT

MIXTURE – FULL LEAN / IDLE CUTOFF

FUEL SELECTOR – OFF

MASTER SWITCH – OFF

CABIN HEAT & AIR – OFF *Except Overhead Vents*

INCREASE AIRSPEED TO EXTINGUISH – LAND ASAP

ENGINE FIRE DURING START

CONTINUE CRANKING ENGINE

IF START – RUN A FEW SECONDS - SHUTDOWN - INSPECT

IF NO START – IDLE MIXTURE CUTOFF & FUEL SELECTOR - OFF

THROTTLE – FULL OPEN

CONTINUE CRANKING ENGINE A FEW SECONDS

MASTER & MAGS – OFF

EVACUATE / FIRE EXTINGUISHER

ICING

PITOT HEAT – ON

CARB HEAT – ON

CABIN HEAT & DEFROST – MAXIMUM

STRONGLY CONSIDER 180° TURN

ATTAIN HIGHER OR LOWER ALTITUDE

INCREASE ENGINE SPEED

FLAPS – NOT RECOMMENDED FOR LANDING

LAND FASTER AS NEEDED

OTHER

EXCESSIVE RATE OF CHARGE: Over Voltage Warning Light Will Illuminate If Reaches Approx. 16 Volts. To Reactivate, Turn Both Sides Of The Master Switch Off / Then On Again. If Light Comes On Again, Terminate Flight ASAP.

INSUFFICIENT RATE OF CHARGE: Nonessential Electric – Off / Terminate Flight ASAP.

Local Frequencies:

UNICOM: 122.7 122.725 122.8 122.975 123.0 123.05
MULTICOM: 122.9 (CTAF) 122.75 (Air To Air)
FSS: 122.2
GROUND: 121.3 123.5 121.7 123.9
EMERGENCY: 121.5

RADIO OUT: CHECK CIRCUIT BREAKERS & VOLUME RECYCLE ALTERNATOR SWITCH IF IFR & STILL OUT, SET XPDR TO 7600. (Suggested For VFR If In B, C, D Airspace.)

TOWER SIGNALS	ON GROUND	IN FLIGHT
Steady Green	Cleared For Takeoff	Cleared To Land
Flashing Green	Cleared To Taxi	Return For Landing
Steady Red	Stop	Yield & Continue Circling
Flashing Red	Taxi Clear of Landing Area	Airport Unsafe - Do Not Land
Flashing White	Return To Starting Point	N/A
Alternating Red & Green	Use Extreme Caution	Use Extreme Caution

* *Every Plane Has A Different Empty Weight And Useful Load*

Cessna 172 I,K,L Lycoming: O-320-E2D, 150 HP

* Empty Weight: LBS *(Specific Plane Weight)*

* Max. Useful Load: LBS *(Including Fuel @ 6 lbs/gal)*

Max. Baggage Area: 120 LBS *(Included In Useful Load)*

Max. T.O. Weight: 2300 LBS

Fuel Type: 100 LL (Blue) / 100 (Green) / 80/87 (Red)

Usable Fuel: 38 Gallons (48 L/R Tanks)

Oil Capacity: 8 Quarts (Minimum 6)

Electrical: 12-14 VOLT / 60 AMP

Tire Pressure: Nose - 26 PSI (5.00 x 5) 172 I,K
31 PSI (6.00 x 6) 172 I,K,L
Main - 24 PSI (6.00 x 6) 172 I,K
29 PSI (6.00 x 6) 172 L